


Technical Details:

- Material: LSFOH coated Steel
- Main usage: LSFOH-coated steel spirals are used in industrial settings like factories, power plants, and transportation systems, ensuring cable protection in high-risk environments
- Temp range: -40°C till +110°C
- Protection: IP40 (IP54 with Fixed Gland)
- Standards: BS EN 61386 High Impact Resistance
- Colour: Black (Grey or other color on request)
- Full-Shrink packing



Code	Code		Inner & Outer Dia. (mm.)	Coil Size (mt.)
	Metric	NPT		
OPGSC7-LSFOH	12		7,5-11,5	50
OPGSC9-LSFOH	16	1/4'	9-13	50
OPGSC11-LSFOH	16	3/8'	11-15	50
OPGSC16-LSFOH	20	1/2'	16-20	50
OPGSC21-LSFOH	25	3/4'	21-25	50
OPGSC26-LSFOH	32	1'	26-31	25
OPGSC35-LSFOH		1 1/4'	35-40	25
OPGSC37-LSFOH	40		37-42	25
OPGSC40-LSFOH	50	1 1/2'	40-45	25
OPGSC51-LSFOH	63	2'	51-56	25

* Dimensions may undergo changes and deviations.

WE ALSO STOCK

**FULL RANGE OF
CONTRACTOR PACKS
SEE PAGES 42-43**

